

low profile downlights

ELTE

Mounting:

- recessed (RCS)
- surface mounted (SFM)

Housing: aluminum

Diffuser: PMMA, opal

Trim Colors:

01-white matte

*other colors are available on request

LED: SMD 2835

CRI: 80-95

AC Volt: 165-265V

Frequency: 50/60Hz

Color temperature, K:

CT35-3500k

CT45-4500k

CT65-6500k

Note: *Lm data given is based on 6500k

LED driver options:

ND - non-dimmable

PH - phase dimmable

010V - 0-10V dimmable

DALI - compatible

Ambient Temp: -20°... +50°

Application: indoors:
residential, hotels, schools
kitchens, offices, class-rooms,
corridors, lift lobbies, etc.


Ordering Guide:

02.54.104.01.08+RN.RCS+01+CT35+ND

(item+round recessed+trim color+LED CCT+non-dimmable driver)






square recessed
(SQ.RCS)




Ref Code	Watt	Lm(±)	Dia(LxL)xHxC.O.
02.54.104.01.08	8W	850	103(103x103)x33x95
02.54.105.01.14	14W	1500	145(145x145)x33x135
02.54.106.01.22	22W	2200	170(170x170)x33x160



round recessed
(RN.RCS)






round recessed
(RN.RCS)




Ref Code	Watt	Lm(±)	Dia(LxL)xHxC.O.
02.54.107.01.08	8W	850	123(123x123)x47x105
02.54.108.01.14	14W	1500	164(164x164)x47x150
02.54.109.01.22	22W	2200	189(189x189)x47x175



square recessed
(SQ.RCS)





round recessed
(RN.RCS)



Ref Code	Watt	Lm(±)	Dia(LxL)xHxC.O.
02.54.110.01.08	8W	850	110(110x110)x26x100
02.54.111.01.14	14W	1500	160(160x160)x26x150
02.54.112.01.22	22W	2200	185(185x185)x26x175



square recessed
(SQ.RCS)



Note: * other trim colors are available on request